

Crackstop® F6

Fibrillated Fibre

Adfil nv

Industriestraat 39, 9240 Zele, Belgium

info@adfil.com / www.adfil.com

Factory code:	02 / 11
AVCP System:	3
Class:	Ib
Notified Lab:	1136

Intended use: for non-structural use in mortar, grout and concrete

Product code:	F5019P0631
----------------------	------------

Essential Characteristics	Standard	Performance	Tolerance
Length	EN 14889-2:2006	6 mm	+/-1,5 mm
Linear Density	EN 14889-2:2006	720 tex	+/-72 tex
Equivalent Diameter	EN 14889-2:2006	1 mm	+0,05 mm
Tensile strength	EN 14889-2:2006	272 MPa	-54 MPa
Tenacity	EN 14889-2:2006	30 cN/tex	-6 cN/tex
Vebe time - 0,6kg	EN 14889-2:2006	n.p.d.	
Vebe time - 0,75kg	EN 14889-2:2006	n.p.d.	
Vebe time - 0,9kg	EN 14889-2:2006	6,3 (5,7) s	
Vebe time - 0,91kg	EN 14889-2:2006	n.p.d.	
Vebe time - 1,0kg	EN 14889-2:2006	n.p.d.	
Vebe time - 1,2kg	EN 14889-2:2006	n.p.d.	

- n.p.d. = no performance determined

The performance of the product identified above is in conformity with the declared performance in above table.
 This declaration of performance is issued under the sole responsibility of Adfil NV

Zele, Belgium

5/05/2025

 Els Van Nimmen
 Quality Department

